

## Bowl tipper HK 150

HK 150  
Bowl tipper

1/2  
14.09.2009

### Device for lifting and tipping of wheel-out dough bowls.

#### Characteristics:

The load-bearing construction, the transport mechanism and the drive of the lifting and tipping device "HK 150" are of extremely robust design. Power reserves ensure that the lifting process is always uniform and safe, irrespective of the bowl filling capacity.

- Tipping direction: Overhead
- Lifting capacity: up to 1.000 kg
- Tipping height: approx. 1.800 mm

#### Advantages

**Very solid construction of all modules High Quality Made in Germany**

- High production and investment security
- Sturdy mobile frame (optional) for flexible operating areas



## Bowl tipper HK 150

**HK 150**  
Bowl tipper

2/2  
14.09.2009

### Specification

Standard Version

#### HK 150

- Including standard safety barrier (pipe frame)
- "Downwards" of the lifting platform, only with touched button "Down" possibly
- Stainless steel panelling

### Options

- Fully mobile
- Rail-mounted, additional
- Other tipping heights
- Dough slide
- Mounting for other manufacturers bowl models
- Lifting tubes

### Technical Data

#### Tipping direction

Overhead

#### Lifting capacity

up to 1.000 kg

#### Tipping height

ca. 1.800 mm

#### Connection parameters

400 V; 1,1 kW; CEE 16A plug connector



® = registered trademark

All details non-binding. Subject to change in the course of technical progress. All rights reserved.